

JACA

3000W 230V



TIPO / TYPE



EQUIPAMIENTO / FEATURES



DOTACIÓN / INCLUDED

EMBALAJE / PACKAGING

RECAMBIOS FRECUENTES / FREQUENT SPARE PARTS



Ref. 400001



Ref. 400064



Ref. 400014



Ref. 400040



Ref. 400046



Ref. 400055

MODELO / MODEL

Regulación - Voltaje - Frecuencia / Regulation - Voltage - Frequency

AC 230V Máxima / Maximum

AC 230V Nominal / Rated

Modelo motor/ Engine model

Cilindrada/ Displacement

Tipo de motor / Engine type

Nivel de presión acústica media a 7mts LpA / Acoustic pressure level average at 7mts LpA

Nivel de potencia acústica garantizada LwA acorde 2000/14/EC enmienda 2005/88/EC
Guaranteed sound power level LwA pursuant to 2000/14/EC amended by 2005/88/EC

Tipo de arranque / Startup type

Capacidad tanque combustible / Fuel tank capacity

Consumo hora - Autonomía al 25% 50% 75% carga

Hourly consumption - Autonomy at 25% 50% 75% loads

Capacidad de aceite - Tipo aceite / Oil capacity - Type of oil

Kit de transporte / Transportation kit

Dimensiones sin/con ruedas L x A x Alto (cm) / Dimensions without/with wheels L x W x H (cm)

Peso máquina / bruto embalaje (Kg) / Machine weight / gross packaging (Kg)

Referencia / Reference

JACA

Estabilizador electrónico / Electronic stabilizer - 230V - 50Hz

3000W

2600W

GENERGY SG70

210cc

Gasolina, 4 tiempos OHV refrigeración forzada por aire
Gasoline, 4-stroke OHV, air forced cooling

71dB (A)

96dB (A)

Manual / Recoil

3.6L

(0.8 l/h - 4.5h) (1 l/h - 3.6h) (1.2 l/h - 3h)

0.6L SAE10W30 - SAE10W40

Si, con neumáticos de goma 8" y llanta metálica
Yes, 8" rubber tires and metal rim

60 x 51 x 45 / 70 x 65 x 50

45 / 52

2013011