



ELECTRIC STORAGE
WATER HEATERS

PROMOTEC



ELECTRIC STORAGE WATER HEATERS

- Thermoindicator
- Safety valve
- Flange for easy maintenance
- Light indicator
- Glass ceramic protection
- External regulation
- Magnesium anode
- Thermo cut-off
- High efficiency insulation



PROMOTEC electric storage water heaters are produced by the latest modern technology of glass-ceramic coating of the water tank.

The glass-ceramic protection assures reliable protection against corrosion together with flawless hygiene of the water and guarantees long useful life of the water tank.



State of the art Plasma welding method used for the production of PROMOTEC water heaters' tanks. Stable and higher grade welding process based on lower welding temperature with no using of extra materials. Computerized control assuring high quality.



PROMOTEC		GCV 3035 12 D07 TRC	GCV 5044 15 D07 TRC	GCV 8044 15 D07 TRC	GCV 10044 15 D07 TRC
Volume	[L]	30	50	82	100
Diameter	[mm]	353	440	440	440
Rated power	[W]	1200	1500	1500	1500
Heating time ΔT 45°C (15-60°C)	[h:min]	01:18	01:44	02:51	03:29
Annual consuption of electricity / AEC	[kWh]	571	1421	2693	2687
Energy class		C	C	C	C
Load profile		S	M	L	L
Dimensions					
height	[m]	0.555	0.593	0.843	0.983
width	[m]	0.353	0.440	0.440	0.440
depth	[m]	0.380	0.468	0.468	0.468

Manufacturer:

TESY OOD

Sofia Park, Building 16V, Office 2.1, 2nd Floor
1166 Sofia, Bulgaria

tesy.com

Dealer:

This leaflet is a marketing material not an offer. For specific models, please ask your dealer.

Copyright © All Rights Reserved, v.2 2017 – TESY OOD