



SPLIT 1X1 IX69B



wifi
incluido

Protección
Golden Fin

Función I
Feel

Modo seguridad
temperatura mínima
ambiente

Temporizador
24h

Modo
silencioso

Auto
limpieza

Auto-restart

Desagüe por
ambos lados

MODELOS	INT.	HTWS026IX69B	HTWS035IX69B	HTWS052IX69B	HTWS071IX69B
		HTWS026IX69B-I	HTWS035IX69B-I	HTWS052IX69B-I	HTWS071IX69B-I
	EXT.	HTWS026IX69B-O	HTWS035IX69B-O	HTWS052IX69B-O	HTWS071IX69B-O
CÓDIGO EAN		8435483874749	8435483874657	8435483874688	8435483874718

Alimentación eléctrica	V,F,Hz	220-240V (1 Fase~ 50Hz) / Unidad exterior			
------------------------	--------	---	--	--	--

RENDIMIENTO					
Capacidad refrigeración	Capacidad	kW	2,6(0,6~3,1)	3,4(0,8~3,8)	5,1(1,3~5,3)
		Btu/h	8866(2046~10571)	11594(2728~12958)	17391(4433~18073)
	Consumo	W	870(100~1600)	1340(200~1500)	1680(280~1800)
	Corriente	A	4,0	5,9	7,5
	SEER	W/W	6,1	6,2	6,4
Capacidad calefacción	Clasificación energética	Frío	A++	A++	A++
	Capacidad	kW	2,61(0,8~3,4)	3,5(0,8~4,0)	5,2(1,3~5,3)
		Btu/h	8900(2728~11594)	11935(2728~13640)	17732(4433~18073)
	Consumo	W	630(300~1600)	950(200~1400)	1430(220~1500)
	Corriente	A	3,0	4,1	6,4
Capacidad calefacción	SCOP	W/W	4,0	4,0	4,0
	Clasificación energética	Calor	A+	A+	A+

CARACTERÍSTICAS					
Unidad interior	Potencia sonora	dB(A)	52	54	56
	Presión sonora (H/L/M/S)	dB(A)	35/32/31/21	37/34/32/23	39/36/34/24
	Caudal de aire (H/L/M/S)	m3/h	500/430/380/320	600/530/480/420	860/780/700/620
	Rango de temp. Seleccionable	°C	17 ~ 32	17 ~ 32	17 ~ 32
Unidad exterior	Potencia sonora	dB(A)	59	61	62
	Presión sonora	dB(A)	46	48	49
	Caudal de aire	m3/h	1550	1550	2300
	Temperatura de operación frío/calor	°C	-15 ~ 50/-15 ~ 30	-15 ~ 50/-15 ~ 30	-15 ~ 50/-15 ~ 30
Refrigerante	Tipo/Carga	R32/kg	0,46	0,57	0,56
	Carga adicional >5m	g/m	20	20	20

DIMENSIONES Y PESO					
Unidad interior	Dimensiones netas (AnxAlxPr)	mm	690x283x199	750x285x200	900x310x225
	Dimensiones brutas (AnxAlxPr)	mm	760x347x277	820x347x277	970x382x302
	Peso neto / bruto	kg	7,0/9,0	7,5/10,5	10,0/13,5
Unidad exterior	Dimensiones netas (AnxAlxPr)	mm	649x450x232	649x450x232	708x530x258
	Dimensiones brutas (AnxAlxPr)	mm	760x510x315	760x510x315	825x595x345
	Peso neto / bruto	kg	18,5/21,0	18,5/21,0	22,0/25,0

CONEXIONES					
Tubería frigorífica	Líquido-Gas	Pulg.	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"
	Longitud máx.	m	20	20	25
	Desnivel máx.	m	10	10	15
Conexiones eléctricas	Alimentación	mm	2x1,5+T	2x1,5+T	2x1,5+T
	Interconexión	mm	4x1,5+T	4x1,5+T	4x1,5+T